

SUSPENSION SETUP

SUPERFOXY SUPER ENDURO

Fork: Fox 38 29 Float GRIP RHYTHM, 170mm

Follow Fox 38 29 Float GRIP RHYTHM recommended settings on the bottom right back side of the casting.
Mondraker recommended Fox 38 29 Float fork settings based on rider weight and Super Enduro application:

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	51	open	16
129,8-136,4lbs / 59-62 kg	55	open	16-15
138,6-145,2lbs / 63-66 kg	59	open	15-14
147,4-154lbs / 67-70 kg	63	open	14-13
156,2-162,8lbs / 71-74 kg	67	open	13-12
165-171,6lbs / 75-78 kg	71	open	12-11
173,8-180,4lbs / 79-82 kg	75	open	11-10
182,6-189,2lbs / 83-86 kg	79	open	10-9
191,4-198lbs / 87-90 kg	83	open	9-8
200,2-206,8lbs / 91-94 kg	87	open	8-7
209-215,6lbs / 95-98 kg	91	open	7-6
217,8-224,4lbs / 99-102 kg	95	open	6-5
226,6-233,2lbs / 103-106 kg	99	open	5-4
235,4-242lbs / 107-110 kg	103	open	4-3
244,2-250,8lbs / 111-114 kg	107	open	3-2
>253-319lbs / >115-145 kg	111	open	2-1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox DHX Performance

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	130	open	11
129,8-136,4lbs / 59-62 kg	138	open	10
138,6-145,2lbs / 63-66 kg	146	open	9
147,4-154lbs / 67-70 kg	154	open	9-8
156,2-162,8lbs / 71-74 kg	162	open	8
165-171,6lbs / 75-78 kg	170	open	8-7
173,8-180,4lbs / 79-82 kg	178	open	7
182,6-189,2lbs / 83-86 kg	186	open	7-6
191,4-198lbs / 87-90 kg	194	open	6
200,2-206,8lbs / 91-94 kg	202	open	6-5
209-215,6lbs / 95-98 kg	210	open	5
217,8-224,4lbs / 99-102 kg	218	open	5-4
226,6-233,2lbs / 103-106 kg	226	open	4
235,4-242lbs / 107-110 kg	234	open	4-3
244,2-250,8lbs / 111-114 kg	242	open	3
>253-319lbs / >115-145 kg	250	open	2

*Settings based on Super Enduro application and 30-35% recommended sag