

SUSPENSION SETUP

SUMMUM MULLET DOWNHILL

Fork: Boxxer Select , 200 mm

Follow Boxxer Select recommended settings on the bottom right back side of the casting.
Mondraker recommended Boxxer Select settings based on rider weight and Downhill application:

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	49	open	16
129,8-136,4lbs / 59-62 kg	52	open	16-15
138,6-145,2lbs / 63-66 kg	55	open	15-14
147,4-154lbs / 67-70 kg	58	open	14-13
156,2-162,8lbs / 71-74 kg	61	open	13-12
165-171,6lbs / 75-78 kg	64	open	12-11
173,8-180,4lbs / 79-82 kg	67	open	11-10
182,6-189,2lbs / 83-86 kg	70	open	10-9
191,4-198lbs / 87-90 kg	73	open	9-8
200,2-206,8lbs / 91-94 kg	76	mid	8-7
209-215,6lbs / 95-98 kg	79	mid	7-6
217,8-224,4lbs / 99-102 kg	82	mid	6-5
226,6-233,2lbs / 103-106 kg	85	mid	5-4
235,4-242lbs / 107-110 kg	88	mid	4-3
244,2-250,8lbs / 111-114 kg	91	mid	3-2
>253-319lbs / >115-145 kg	94	mid	2-1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Vvid Coil RC

Size M: 450 lbs Size L: 500 lbs Size XL: 550 lbs

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	SPRING RATE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	lbs	HBO	LSR
<121-128lbs / <55-58 kg	450	open	14
129,8-136,4lbs / 59-62 kg	450	open	14-13
138,6-145,2lbs / 63-66 kg	450	open	13-12
147,4-154lbs / 67-70 kg	450	open	12-11
156,2-162,8lbs / 71-74 kg	450	open	11-10
165-171,6lbs / 75-78 kg	500	mid	10-9
173,8-180,4lbs / 79-82 kg	500	mid	9-8
182,6-189,2lbs / 83-86 kg	500	mid	8-7
191,4-198lbs / 87-90 kg	500	mid	7-6
200,2-206,8lbs / 91-94 kg	500	mid	6-5
209-215,6lbs / 95-98 kg	500	mid	5-4
217,8-224,4lbs / 99-102 kg	550	close	4-3
226,6-233,2lbs / 103-106 kg	550	close	3-2
235,4-242lbs / 107-110 kg	550	close	2-1
244,2-250,8lbs / 111-114 kg	550	close	2-1
>253-319lbs / >115-145 kg	550	close	1

*Settings based on Downhill application and 30-35% recommended sag