

SUSPENSION SETUP

CRAFTY CARBON RR SL E-MTB ENDURO

Fork: Fox 36 29 Float GRIPX2 Factory Kashima, 160mm

Follow Fox 36 Float GRIPX2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Fox 36 Float GRIPX2 Factory Kashima fork settings based on rider weight and E-MTB Enduro application:

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	psi	HSR	LSR	HSC	LSC
<121-128lbs / <55-58 kg	63	7	16	8	18
129,8-136,4lbs / 59-62 kg	67	7	15	8	17
138,6-145,2lbs / 63-66 kg	71	7-6	14	8	16
147,4-154lbs / 67-70 kg	75	7-6	13	8-7	15
156,2-162,8lbs / 71-74 kg	79	6-5	12	7	14
165-171,6lbs / 75-78 kg	83	6-5	11	7-6	13
173,8-180,4lbs / 79-82 kg	87	5-4	10	6	12
182,6-189,2lbs / 83-86 kg	91	5-4	9	6-5	11
191,4-198lbs / 87-90 kg	95	4-3	8	5	10
200,2-206,8lbs / 91-94 kg	99	4-3	7	5-4	9
209-215,6lbs / 95-98 kg	103	3-2	6	4	8
217,8-224,4lbs / 99-102 kg	107	3-2	5	4-3	7
226,6-233,2lbs / 103-106 kg	111	2-1	4	3	6
235,4-242lbs / 107-110 kg	115	2-1	3	3-2	5
244,2-250,8lbs / 111-114 kg	119	1	2	2	4
>253-319lbs / >115-145 kg	123	1	1	1	3

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox Float Factory Kashima EVOL

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	120	1	8
129,8-136,4lbs / 59-62 kg	128	1	7
138,6-145,2lbs / 63-66 kg	136	1	6
147,4-154lbs / 67-70 kg	144	1	6-5
156,2-162,8lbs / 71-74 kg	152	2	5
165-171,6lbs / 75-78 kg	160	2	5-4
173,8-180,4lbs / 79-82 kg	168	2	5-4
182,6-189,2lbs / 83-86 kg	176	2	4
191,4-198lbs / 87-90 kg	184	2	4-3
200,2-206,8lbs / 91-94 kg	192	2	4-3
209-215,6lbs / 95-98 kg	200	2	3
217,8-224,4lbs / 99-102 kg	208	2	3-2
226,6-233,2lbs / 103-106 kg	216	3	3-2
235,4-242lbs / 107-110 kg	224	3	2
244,2-250,8lbs / 111-114 kg	232	3	2
>253-319lbs / >115-145 kg	240	3	1

*Settings based on Enduro application and 30-35% recommended sag