

SUSPENSION SETUP

DUNE RR Light e-MTB

Fork: Fox Podium 29 GRIPX2 Factory Kashima, 170mm

Follow Fox Podium 29 GRIPX2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Öhlins RXF38 M.2 fork settings based on rider weight and Super Enduro application:

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	psi	HSC	HSR	LSC	LSR
<121-128lbs / <55-58 kg	60	8	7	18	16
129,8-136,4lbs / 59-62 kg	65	8	7	17	15
138,6-145,2lbs / 63-66 kg	70	8-7	7-6	16	14
147,4-154lbs / 67-70 kg	75	7	7-6	15	13
156,2-162,8lbs / 71-74 kg	80	7-6	6-5	14	12
165-171,6lbs / 75-78 kg	85	6	6-5	13	11
173,8-180,4lbs / 79-82 kg	90	6-5	5-4	12	10
182,6-189,2lbs / 83-86 kg	95	5	5-4	11	9
191,4-198lbs / 87-90 kg	100	5-4	4-3	10	8
200,2-206,8lbs / 91-94 kg	105	4	4-3	9	7
209-215,6lbs / 95-98 kg	110	4-3	3-2	8	6
217,8-224,4lbs / 99-102 kg	115	3	3-2	7	5
226,6-233,2lbs / 103-106 kg	120	3-2	2-1	6	4
235,4-242lbs / 107-110 kg	125	2	2-1	5	3
244,2-250,8lbs / 111-114 kg	130	2-1	1	4	2
>253-319lbs / >115-145 kg	135	1	1	3	1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox DHX2 Factory Kashima

Size S: 350 lbs Size M: 400 lbs Size L: 450 lbs Size XL: 500 lbs

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	SPRING RATE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	lbs	HSC	LSC	HSR	LSR
<121-128lbs / <55-58 kg	350	10	15	7	14
129,8-136,4lbs / 59-62 kg	350	10-9	14	7	13
138,6-145,2lbs / 63-66 kg	350	10-9	13	7-6	12
147,4-154lbs / 67-70 kg	350	9	12	7-6	12
156,2-162,8lbs / 71-74 kg	350	9-8	11	6-5	11
165-171,6lbs / 75-78 kg	400	9-8	10	6-5	11
173,8-180,4lbs / 79-82 kg	400	8	9	5-4	10
182,6-189,2lbs / 83-86 kg	400	8-7	8	5-4	10
191,4-198lbs / 87-90 kg	400	8-7	7	4-3	9
200,2-206,8lbs / 91-94 kg	450	7	6	4-3	8
209-215,6lbs / 95-98 kg	450	7-6	5	3-2	7
217,8-224,4lbs / 99-102 kg	450	7-6	4	3-2	6
226,6-233,2lbs / 103-106 kg	500	6	3	2-1	5
235,4-242lbs / 107-110 kg	500	6-5	2	2-1	4
244,2-250,8lbs / 111-114 kg	500	6-5	1	1	3
>253-319lbs / >115-145 kg	500	5	1	1	2

*Settings based on Super Enduro application and 30-35% recommended sag