

SUSPENSION SETUP

ZENDIT RR S E-MTB ENDURO

Fork: Fox Podium 29 Float GRIPX2 Factory Kashima, 170mm

Follow Fox Podium Float GRIP X2 Factory Kashima recommended settings on the bottom right back side of the casting. Mondraker recommended Fox Podium Float GRIP X2 Factory Kashima fork settings based on rider weight and E-MTB Enduro application:

SAG		RECOMMENDED SETTING			
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED			
lbs / kg	psi	HSC	LSC	HSR	LSR
<121-128lbs / <55-58 kg	60	8	18	7	16
129,8-136,4lbs / 59-62 kg	65	8	17	7	15
138,6-145,2lbs / 63-66 kg	70	8-7	16	7-6	14
147,4-154lbs / 67-70 kg	75	7	15	7-6	13
156,2-162,8lbs / 71-74 kg	80	7-6	14	6-5	12
165-171,6lbs / 75-78 kg	85	6	13	6-5	11
173,8-180,4lbs / 79-82 kg	90	6-5	12	5-4	10
182,6-189,2lbs / 83-86 kg	95	5	11	5-4	9
191,4-198lbs / 87-90 kg	100	5-4	10	4-3	8
200,2-206,8lbs / 91-94 kg	105	4	9	4-3	7
209-215,6lbs / 95-98 kg	110	4-3	8	3-2	6
217,8-224,4lbs / 99-102 kg	115	3	7	3-2	5
226,6-233,2lbs / 103-106 kg	120	3-2	6	2-1	4
235,4-242lbs / 107-110 kg	125	2	5	2-1	3
244,2-250,8lbs / 111-114 kg	130	2-1	4	1	2
>253-319lbs / >115-145 kg	135	1	3	1	1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox Float X Factory Kashima EVOL LV

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	147	9	10
129,8-136,4lbs / 59-62 kg	155	8	9
138,6-145,2lbs / 63-66 kg	163	7	8
147,4-154lbs / 67-70 kg	171	7-6	7
156,2-162,8lbs / 71-74 kg	179	6	6
165-171,6lbs / 75-78 kg	187	6-5	6
173,8-180,4lbs / 79-82 kg	195	5	5
182,6-189,2lbs / 83-86 kg	203	5-4	4
191,4-198lbs / 87-90 kg	211	4	4-3
200,2-206,8lbs / 91-94 kg	219	4-3	4
209-215,6lbs / 95-98 kg	227	3	3
217,8-224,4lbs / 99-102 kg	235	3-2	3-2
226,6-233,2lbs / 103-106 kg	243	2	2
235,4-242lbs / 107-110 kg	251	2-1	2
244,2-250,8lbs / 111-114 kg	259	1	1
>253-319lbs / >115-145 kg	267	1	1

*Settings based on Enduro application and 30-35% recommended sag