

SUSPENSION SETUP

ZENDIT S E-MTB ENDURO

Fork: RockShox ZEB Base 29, Delta RC, 170mm

Follow RockShox ZEB Base 29 recommended settings on the bottom right back side of the casting. Mondraker recommended RockShox ZEB Base 29 fork settings based on rider weight and E-MTB Enduro application:

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	50	-2	14
129,8-136,4lbs / 59-62 kg	54	-2	13
138,6-145,2lbs / 63-66 kg	58	-2	12
147,4-154lbs / 67-70 kg	62	-1	11
156,2-162,8lbs / 71-74 kg	66	-1	10
165-171,6lbs / 75-78 kg	70	-1	10-9
173,8-180,4lbs / 79-82 kg	74	0	9
182,6-189,2lbs / 83-86 kg	78	0	9-8
191,4-198lbs / 87-90 kg	82	0	8
200,2-206,8lbs / 91-94 kg	86	0	8-7
209-215,6lbs / 95-98 kg	90	1	7
217,8-224,4lbs / 99-102 kg	94	1	7-6
226,6-233,2lbs / 103-106 kg	98	1	6
235,4-242lbs / 107-110 kg	102	2	6-5
244,2-250,8lbs / 111-114 kg	106	2	5
>253-319lbs / >115-145 kg	110	2	5

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: RockShox Super Deluxe Select

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	160	open	12
129,8-136,4lbs / 59-62 kg	170	open	11
138,6-145,2lbs / 63-66 kg	180	open	10
147,4-154lbs / 67-70 kg	190	open	9
156,2-162,8lbs / 71-74 kg	200	open	8
165-171,6lbs / 75-78 kg	210	open	7
173,8-180,4lbs / 79-82 kg	220	open	6
182,6-189,2lbs / 83-86 kg	230	open	5
191,4-198lbs / 87-90 kg	240	open	5-4
200,2-206,8lbs / 91-94 kg	250	open	4
209-215,6lbs / 95-98 kg	260	open	4-3
217,8-224,4lbs / 99-102 kg	270	open	3
226,6-233,2lbs / 103-106 kg	280	open	3-2
235,4-242lbs / 107-110 kg	290	open	2
244,2-250,8lbs / 111-114 kg	300	open	2-1
>253-319lbs / >115-145 kg	310	open	1

*Settings based on Enduro application and 30-35% recommended sag